

# Offline S

OFL 047 169 038S 8040 10 99 OP 40 TK




Surface Mounted Linear Luminary




|                                      |                           |
|--------------------------------------|---------------------------|
| <b>Luminaire Group</b>               | Linear                    |
| <b>Mounting Type</b>                 | Surface Mounted           |
| <b>Luminary Color</b>                | RAL 9016 - RAL 9010       |
| <b>Housing</b>                       | Aluminum extruded profile |
| <b>Optics</b>                        | Opal Diffuser             |
| <b>Light Source</b>                  | LED                       |
| <b>Electrical Protection Class</b>   | CLASS II                  |
| <b>IP</b>                            | 40                        |
| <b>IK</b>                            | 03                        |
| <b>Operating Temperature</b>         | -20°C / +40°C             |
| <b>Luminous Flux</b>                 | 2660                      |
| <b>Consumption Power</b>             | 38                        |
| <b>Luminaire Efficiency</b>          | 70 lm/W                   |
| <b>Color Rendering (CRI)</b>         | >80                       |
| <b>Light Color Temperature (CCT)</b> | 2700K/3000K/4000K/6500K   |
| <b>Color Tolerance</b>               | < 3 SDCM                  |
| <b>Driver Type</b>                   | On/Off                    |
| <b>Driver Brand</b>                  | Tridonic                  |
| <b>LED Brand</b>                     | Samsung                   |
| <b>Input Voltage / Frequency</b>     | 220-240 V AC 50/60 Hz     |
| <b>Power Factor</b>                  | >0.9                      |
| <b>Surge</b>                         | 1kV                       |
| <b>THD (AKIM)</b>                    | >%20                      |
| <b>LED life</b>                      | >70.000 hours             |

Technical Drawing



Photometric Curve



| SKU | Product Code                         | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics      | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|-------------|-----------------|
|     | OFL 047 169 038S 8040 10 99 OP 40 TK | 38        | 2660               | >80 | 4000    | 120° / Opal | 1690x47x70      |

[www.atellighting.com](http://www.atellighting.com)