

Outline Cent

OUT 100 224 054A 8030 10 99 OP 40 LC




Recessed Linear Luminary




| | |
|--------------------------------------|---------------------------|
| Luminaire Group | Linear |
| Mounting Type | Recessed |
| Luminary Color | RAL 9010 - RAL 9005 |
| Housing | Aluminum extruded profile |
| Optics | Opal Difüzör & Lens 35° |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 40 |
| IK | 03 |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 3870 |
| Consumption Power | 54 |
| Luminaire Efficiency | 70 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K/3000K/4000K/6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >70.000 hours |

Technical Drawing



Photometric Curve



Outline Cent

OUT 100 224 054A 8030 10 99 OP 40 LC



Recessed Linear Luminary

| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|--------|-----------------|
| | OUT 100 224 054A 8030 10 99 OP 40 LC | 54 | 3870 | >80 | 4000 | 35° | 2240x47x70 |