

# Grilliato

GRL 015 004 007B 8040 10 99 OP 20 00




Recessed Concept Ceiling Luminaire




|                                      |   |
|--------------------------------------|---|
| <b>Luminaire Group</b>               | Concept Ceiling                               |
| <b>Mounting Type</b>                 | Recessed                                      |
| <b>Luminaire Color</b>               | RAL 9005 - RAL 9010                           |
| <b>Housing</b>                       | Aluminum DKP Sheet                            |
| <b>Optics</b>                        | Opal Diffuser                                 |
| <b>Electrical Protection Class</b>   | CLASS II                                      |
| <b>Operating Temperature</b>         | -20°C / +40°C                                 |
| <b>Luminous Flux</b>                 | 630   |
| <b>Consumption Power</b>             | 7   |
| <b>Luminaire Efficiency</b>          | 90 lm/W                                       |
| <b>Color Rendering (CRI)</b>         | >80   |
| <b>Light Color Temperature (CCT)</b> | 2700K/3000K/4000K/6500K                       |
| <b>Color Tolerance</b>               | < 3 SDCM                                      |
| <b>Driver Type</b>                   | On/Off  |
| <b>Driver Brand</b>                  | Tridonic                                      |
| <b>LED Brand</b>                     | Samsung                                       |
| <b>Input Voltage / Frequency</b>     | 220-240 V AC 50/60 Hz                         |
| <b>Power Factor</b>                  | >0.9  |
| <b>Surge</b>                         | 1kV   |
| <b>THD (AKIM)</b>                    | >%20  |
| <b>LED life</b>                      | >100.000 hours                                |
| <b>Option</b>                        | On-Off / Dali / 1-10V / With<br>Emergency Kit |

Technical Drawing



Photometric Curve



| SKU | Product Code                         | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics             | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|--------------------|-----------------|
|     | GRL 015 004 007B 8040 10 99 OP 20 00 | 7         | 630                | >80 | 4000    | 180° Opal Diffuser | 154x154x69      |

[www.atellighting.com](http://www.atellighting.com)