

# Make Mid & Make Sid

MKS 006 012 005W 8040 10 36 AP 20 00



Track Lighting Luminary




|                                      |                                |
|--------------------------------------|--------------------------------|
| <b>Luminaire Group</b>               | Track Lighting                 |
| <b>Luminary Color</b>                | RAL 9005 - RAL 9006 - RAL 9010 |
| <b>Housing</b>                       | Aluminum Injection             |
| <b>Optics</b>                        | GU10/MR16                      |
| <b>Light Source</b>                  | LED                            |
| <b>Electrical Protection Class</b>   | CLASS II                       |
| <b>IP</b>                            | 20                             |
| <b>IK</b>                            | 02                             |
| <b>Operating Temperature</b>         | -20°C / +40°C                  |
| <b>Luminous Flux</b>                 |                                |
| <b>Consumption Power</b>             | 5                              |
| <b>Luminaire Efficiency</b>          | - lm/W                         |
| <b>Color Rendering (CRI)</b>         | >80                            |
| <b>Light Color Temperature (CCT)</b> | 2700K/3000K/4000K/6500K        |
| <b>Color Tolerance</b>               | < 3 SDCM                       |
| <b>Driver Type</b>                   | On/Off                         |
| <b>Driver Brand</b>                  | Tridonic                       |
| <b>LED Brand</b>                     | Samsung                        |
| <b>Input Voltage / Frequency</b>     | 220-240 V AC 50/60 Hz          |
| <b>Power Factor</b>                  | >0.9                           |
| <b>Surge</b>                         | 1kV                            |
| <b>THD (AKIM)</b>                    | >%20                           |
| <b>LED life</b>                      | >50.000 hours                  |

Technical Drawing



Photometric Curve



| SKU | Product Code                         | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics   | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|----------|-----------------|
|     | MKS 006 012 005W 8040 10 36 AP 20 00 | 5         |                    | >80 | 4000    | 36° GU11 | Ø60x210         |

[www.atellighting.com](http://www.atellighting.com)