

Wally

WLY 005 090 036S 8030 10 30 LN 67 00




Floor Facade & Landscape Luminary



| | |
|--------------------------------------|-----------------------------------|
| Luminaire Group | Facade & Landscape |
| Mounting Type | Floor |
| Luminaire Color | RAL 9005 - RAL 9006 - RAL 9010 |
| Housing | Aluminum Extrusion |
| Optics | 15° 30° 40° Lens & Tempered Glass |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 67 |
| IK | 09 |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 3708 |
| Consumption Power | 36 |
| Luminaire Efficiency | 103 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K/3000K/4000K/6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >70.000 hours |
| Option | On-Off / Dali / 1-10V |

Technical Drawing



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|----------|-----------------|
| | WLY 005 090 036S 8030 10 30 LN 67 00 | 36 | 3708 | >80 | 4000 | 30° Lens | L:900 |

www.atellighting.com