

# Wally

WLY 005 090 036S 8030 10 30 LN 67 00




Floor Facade & Landscape Luminary



|                                      |                                   |
|--------------------------------------|-----------------------------------|
| <b>Luminaire Group</b>               | Facade & Landscape                |
| <b>Mounting Type</b>                 | Floor                             |
| <b>Luminaire Color</b>               | RAL 9005 - RAL 9006 - RAL 9010    |
| <b>Housing</b>                       | Aluminum Extrusion                |
| <b>Optics</b>                        | 15° 30° 40° Lens & Tempered Glass |
| <b>Light Source</b>                  | LED                               |
| <b>Electrical Protection Class</b>   | CLASS II                          |
| <b>IP</b>                            | 67                                |
| <b>IK</b>                            | 09                                |
| <b>Operating Temperature</b>         | -20°C / +40°C                     |
| <b>Luminous Flux</b>                 | 3708                              |
| <b>Consumption Power</b>             | 36                                |
| <b>Luminaire Efficiency</b>          | 103 lm/W                          |
| <b>Color Rendering (CRI)</b>         | >80                               |
| <b>Light Color Temperature (CCT)</b> | 2700K/3000K/4000K/6500K           |
| <b>Color Tolerance</b>               | < 3 SDCM                          |
| <b>Driver Type</b>                   | On/Off                            |
| <b>Driver Brand</b>                  | Tridonic                          |
| <b>LED Brand</b>                     | Samsung                           |
| <b>Input Voltage / Frequency</b>     | 220-240 V AC 50/60 Hz             |
| <b>Power Factor</b>                  | >0.9                              |
| <b>Surge</b>                         | 1kV                               |
| <b>THD (AKIM)</b>                    | >%20                              |
| <b>LED life</b>                      | >70.000 hours                     |
| <b>Option</b>                        | On-Off / Dali / 1-10V             |

Technical Drawing



| SKU | Product Code                         | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics   | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|----------|-----------------|
|     | WLY 005 090 036S 8030 10 30 LN 67 00 | 36        | 3708               | >80 | 4000    | 30° Lens | L:900           |

[www.atellighting.com](http://www.atellighting.com)