


Woven

WOV 150 100 010S 8040 10 99 OP 66 00

Concrete Park & Garden Luminary



Luminaire Group	Park & Garden
Mounting Type	Concrete
Luminaire Color	RAL 9006 - RAL 9005 - RAL 9010
Housing	Aluminum Body
Optics	Reflector
Light Source	LED
Electrical Protection Class	CLASS II
IP	66
IK	08
Operating Temperature	-20°C / +40°C
Luminous Flux	1180
Consumption Power	9
Luminaire Efficiency	131 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.95
Surge	8/9kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V

Technical Drawing



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	WOV 150 100 010S 8040 10 99 OP 66 00	9	1180	>80	4000	360° Opal Diffuser	Ø125x1500

www.atellighting.com