


Hidline Corner



HID 022 100 010S 8030 10 99 OP 44 00



Surface Mounted Cove Lighting Luminaire



| | |
|--------------------------------------|-----------------------|
| Luminaire Group | Cove Lighting |
| Mounting Type | Surface Mounted |
| Housing | Aluminum Profile |
| Optics | Opal Diffuser |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 20 |
| IK | 03 |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 960 |
| Consumption Power | 12 |
| Luminaire Efficiency | 80 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 3500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >70.000 hours |
| Option | On-Off / Dali / 1-10V |



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|-----------------------------------|-----------------|
| | HID 022 100 010S 8030 10 99 OP 44 00 | 12 | 960 | >80 | 4000 | 130° Polycarbonat e Acrylic | 1000x22x22 |

www.atellighting.com