

Luma



LMA 005 150 046S 8040 10 99 OP 65 00



Surface Mounted Industrial Luminaire



| | |
|--------------------------------------|--|
| Luminaire Group | Industrial |
| Mounting Type | Surface Mounted |
| Housing | Aluminum Anodized Coating |
| Optics | Opal PC Diffuser |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 65 |
| IK | 09 |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 5658 |
| Consumption Power | 46 |
| Luminaire Efficiency | 123 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K / 3000K / 4000K / 6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | 70.000 hours |
| Option | On-Off / Dali / 1-10V / With Emergency Kit |



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|-----------------------|-----------------|
| | LMA 005 150 046S 8040 10 99 OP 65 00 | 46 | 5658 | >80 | 4000 | 120° Opal PC Diffuser | 84x75x1500 |

www.atellighting.com