

Pere S & M





Pendant Luminary



Luminaire Group	Pendant
Mounting Type	Pendant
Luminaire Color	RAL 9005 - RAL 9006 - RAL 9010
Housing	DKP Sheet
Optics	Halogen Bulb
Light Source	E27
Electrical Protection Class	CLASS II
IP	20
IK	02
Operating Temperature	-20°C / +40°C
Luminous Flux	
Consumption Power	150 W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>16.000 hours
Option	On-Off / Dali / 1-10V / With Emergency Kit

Technical Drawing



Pere S & M



Pendant Luminary

SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
19000205	PER 035 043 150P 0040 10 99 AP 40 00	150		>80	4000	120° Diffuser	Ø350x430
19000213	PER 045 055 150P 0040 10 99 AP 40 00	150		>80	4000	120° Diffuser	Ø450x555