


# Full Moon





## Recessed Luminary




<b>Luminaire Group</b>	Recessed
<b>Mounting Type</b>	Recessed
<b>Luminaire Color</b>	RAL 9005 - RAL 9006 - RAL 9010
<b>Housing</b>	DKP Sheet
<b>Optics</b>	Opal Diffuser
<b>Light Source</b>	LED
<b>Electrical Protection Class</b>	CLASS II
<b>IP</b>	40
<b>IK</b>	02
<b>Operating Temperature</b>	-20°C / +40°C
<b>Luminous Flux</b>	3650 lm / 5730 lm / 6290 lm
<b>Consumption Power</b>	25 W / 35 W / 48 W
<b>Luminaire Efficiency</b>	146 lm/W
<b>Color Rendering (CRI)</b>	>80
<b>Light Color Temperature (CCT)</b>	2700K/3000K/4000K/6500K
<b>Color Tolerance</b>	< 3 SDCM
<b>Driver Type</b>	On/Off
<b>Driver Brand</b>	Tridonic
<b>LED Brand</b>	Samsung
<b>Input Voltage / Frequency</b>	220-240 V AC 50/60 Hz
<b>Power Factor</b>	>0.9
<b>Surge</b>	1kV
<b>THD (AKIM)</b>	>%20
<b>LED life</b>	>70.000 hours
<b>Option</b>	On-Off / Dali / 1-10V / With Emergency Kit

Technical Drawing





Photometric Curve



# Full Moon



## Recessed Luminary



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
13000085□	FLM 038 010 025A 8040 10 99 OP 40 00	25	3650	>80	4000	120° Opal Diffuser	Ø380
13000109□	FLM 046 010 035A 8040 10 99 OP 40 00	35	5730	>80	4000	120° Opal Diffuser	Ø460
13000133□	FLM 066 010 048A 8040 10 99 OP 40 00	48	6290	>80	4000	120° Opal Diffuser	Ø660