

Conus




Pendant Wood & Concrete Products Luminary



| | |
|--------------------------------------|--------------------------|
| Luminaire Group | Wood & Concrete Products |
| Mounting Type | Pendant |
| Luminaire Color | RAL 7035 - |
| Housing | Concrete and Wood |
| Optics | LED Bulb |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 20 |
| IK | 02 |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | |
| Consumption Power | 25 W |
| Luminaire Efficiency | - lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K/3000K/4000K/6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >20.000 hours |

Technical Drawing



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--|-----------|--------------------|-----|---------|-----------|-----------------|
| | CRO 090 019 025P 8040 10 GU10 20 00 C1 | 25 | | >80 | 4000 | 100° GU10 | Ø446x206 |